

# 10343 1000V LEVER-ACTION CONNECTOR

## 1000V/75A

### 10343-XXXXX- XXX



**CONDUCTORS:**  
**(3) POWER**  
**(1) GROUND**  
**(1/2) PILOTS**



1. Configuration	2. Color	
101 = Female Panel Mount Single Pilot – Insert Only 102 = Female Panel Mount Dual Pilot – Insert Only 401 = Female Cable Attachable Single Pilot 402 = Female Cable Attachable Dual Pilot 501 = Male Cable Attachable Single Pilot 502 = Male Cable Attachable Dual Pilot 601 = Male Panel Mount Single Pilot – Insert Only 602 = Male Panel Mount Dual Pilot – Insert Only 1201 = Female Panel Mount Single Pilot 1202 = Female Panel Mount Dual Pilot 1601 = Male Panel Mount Single Pilot 1602 = Male Panel Mount Dual Pilot G = Grounded	BLU = Standard Blue RED = Red BLK = Black WHT = White ORG = Orange GRN = Green YEL = Yellow	<p><u>Corporate Office</u>                      11782 Country Club Road                      West Frankfort, Illinois 62896                      Tel 618-932-2151                      Fax 618-937-2715</p> <p><u>US Sales</u>                      Heath Dotson  <a href="mailto:Heath.dotson@specialmineservices.com">Heath.dotson@specialmineservices.com</a></p> <p><u>International Sales</u>                      Marshall Girtman  <a href="mailto:Marshall.girtman@specailmineservices.com">Marshall.girtman@specailmineservices.com</a></p> <p><u>Canadian Office</u>                      Tel 647-808-0965                      Fax 847-656-5094  <a href="mailto:SMSConnectors@aol.com">SMSConnectors@aol.com</a></p>

Accessories	Male	Female
Panel Mount Shells	A-324289LA	324088LA
Protective Caps	3325656-201	3325656-101
Pilot Short Circuiting Cap – Female Receptacle Only	N/A	8343-701
Cleaning Tool Power/Ground Contacts	43MCT	43FCT
Cleaning Tool Pilot Contacts	43MPCT	43FPCT

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
<b>325298-LA</b>	1.500 – 1.250	1.250 – 1.000	1.000 – 0.750	0.750 – 0.562	N/A
	Not Required	<b>313305-1LA</b>	<b>313305-2LA</b> <small>One (1) Supplied with Connector</small>	<b>313305-3LA</b> <small>One (1) Supplied with Connector</small>	

Spare Parts	Male	Female																		
Grounded Clamp Set	8343-1994MF-1KV	8343-1994MF-1KV																		
Receptable Eye Bolt	8343-1997M	8343-1997F																		
Handle Cable Inline Connector	8343-1995LSS																			
Handle Receptable	8343-1995R																			
Draw Bar Cable Inline Connector	8343-1996LSS																			
Draw Bar Receptable	8343-1996R																			
316 S.S. 45 Degree Box		4543S																		
Premium Hardware Kit: BOM	KIT-43																			
	<table border="1"> <thead> <tr> <th>Description</th> <th>Qty</th> <th>Description</th> <th>Qty</th> <th>Description</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>SS 5/16-24 x 3/8"</td> <td>8</td> <td>YAD1010</td> <td>2</td> <td>HC-36</td> <td>2</td> </tr> <tr> <td>10-24 x 1/2" SMSM</td> <td>2</td> <td>HC-28</td> <td>2</td> <td>1/4-20 x 3/8"</td> <td>2</td> </tr> </tbody> </table>	Description	Qty	Description	Qty	Description	Qty	SS 5/16-24 x 3/8"	8	YAD1010	2	HC-36	2	10-24 x 1/2" SMSM	2	HC-28	2	1/4-20 x 3/8"	2	
Description	Qty	Description	Qty	Description	Qty															
SS 5/16-24 x 3/8"	8	YAD1010	2	HC-36	2															
10-24 x 1/2" SMSM	2	HC-28	2	1/4-20 x 3/8"	2															

#### Ratings

Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
8	75	1000	4X

Wiring Diagram



C CSA US

Certified  
600V

(SMS Rated to 1000V)