

10346 1000V LEVER-ACTION CONNECTOR

10346-XXXXX- XXX

1000V/225A



CONDUCTORS:
(3) POWER
(1) GROUND
(1/2) PILOTS



1. Configuration	2. Color	
101 = Female Cable Attachable Single Pilot	BLK = Standard Black	<p><u>Corporate Office</u> 11782 Country Club Road West Frankfort, Illinois 62896 Tel 618-932-2151 Fax 618-937-2715</p> <p><u>US Sales</u> Heath Dotson Heath.dotson@specialmineservices.com</p> <p><u>International Sales</u> Marshall Girtman Marshall.girtman@specailmineservices.com</p> <p><u>Canadian Office</u> Tel 647-808-0965 Fax 847-656-5094 SMSConnectors@aol.com</p>
102 = Female Cable Attachable Dual Pilot	RED = Red	
201 = Male Cable Attachable Single Pilot	WHT = White	
202 = Male Cable Attachable Dual Pilot	ORG = Orange	
801 = Female Panel Mount Single Pilot	BLU = Blue	
802 = Female Panel Mount Dual Pilot	GRN = Green	
1301 = Male Panel Mount Single Pilot	YEL = Yellow	
1302 = Male Panel Mount Dual Pilot		
1501 = Female Panel Mount Single Pilot – Insert Only		
1502 = Female Panel Mount Dual Pilot – Insert Only		
1601 = Male Panel Mount Single Pilot – Insert Only		
1602 = Male Panel Mount Dual Pilot – Insert Only		
G = Grounded		

Accessories	Male	Female
Panel Mount Shells	A-324232LA	324059LA
Protective Caps	3325656-801	3325656-701
Pilot Short Circuiting Cap – Female Receptacle Only	N/A	8346-301
Cleaning Tool Power/Ground Contacts	46MCT	46FCT
Cleaning Tool Pilot Contacts	46MPCT	46FPCT

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325245	2.375 – 2.125 Not Required	2.125 – 1.937 324153-1	1.937 – 1.750 324153-2	1.750 – 1.562 324153-3	1.562 – 1.375 324153-4
			One (1) Supplied with Connector		One (1) Supplied with Connector

Spare Parts	Male	Female																		
Grounded Clamp Set	8346-1994MF-1KV	8346-1994MF-1KV																		
Receptable Eye Bolt	8346-1997M	8346-1997F																		
Handle Cable Inline Connector	8346-1995LSS	N/A																		
Handle Receptable	8346-1995R	N/A																		
Draw Bar Cable Inline Connector	8346-1996LSS	N/A																		
Draw Bar Receptable	8346-1996R	N/A																		
316 S.S. 45 Degree Box		4546S																		
Premium Hardware Kit: BOM	KIT-46																			
	<table border="1"> <thead> <tr> <th>Description</th> <th>Qty</th> <th>Description</th> <th>Qty</th> <th>Description</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>SS ½-20 x ½" LG</td> <td>8</td> <td>YAD1014</td> <td>2</td> <td>HC-56</td> <td>1</td> </tr> <tr> <td>¼-20 x ½" SMSM</td> <td>2</td> <td>HC-44</td> <td>2</td> <td>¼-20 x 3/8"</td> <td>2</td> </tr> </tbody> </table>	Description	Qty	Description	Qty	Description	Qty	SS ½-20 x ½" LG	8	YAD1014	2	HC-56	1	¼-20 x ½" SMSM	2	HC-44	2	¼-20 x 3/8"	2	
Description	Qty	Description	Qty	Description	Qty															
SS ½-20 x ½" LG	8	YAD1014	2	HC-56	1															
¼-20 x ½" SMSM	2	HC-44	2	¼-20 x 3/8"	2															

Ratings			
Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
2/0	225	1000	4X
Wiring Diagram			



C CSA US
Certified
600V

(SMS Rated to 1000V)