

# 10347 1000V LEVER-ACTION CONNECTOR

## 10347-XXXXX- XXX

## 1000V/325A



**CONDUCTORS:**  
**(3) POWER**  
**(1) GROUND**  
**(1/2) PILOTS**



1. Configuration	2. Color	
101 = Female Cable Attachable Single Pilot 102 = Female Cable Attachable Dual Pilot 201 = Male Cable Attachable Single Pilot 202 = Male Cable Attachable Dual Pilot 801 = Female Panel Mount Single Pilot 802 = Female Panel Mount Dual Pilot 1301 = Male Panel Mount Single Pilot 1302 = Male Panel Mount Dual Pilot 1501 = Female Panel Mount Single Pilot – Insert Only 1502 = Female Panel Mount Dual Pilot – Insert Only 1601 = Male Panel Mount Single Pilot – Insert Only 1602 = Male Panel Mount Dual Pilot – Insert Only G = Grounded	BLK = Standard Black RED = Red WHT = White ORG = Orange BLU = Blue GRN = Green YEL = Yellow	<p><b>Corporate Office</b>                      11782 Country Club Road                      West Frankfort, Illinois 62896                      Tel 618-932-2151                      Fax 618-937-2715</p> <p><b>US Sales</b>                      Heath Dotson  <a href="mailto:Heath.dotson@specialmineservices.com">Heath.dotson@specialmineservices.com</a></p> <p><b>International Sales</b>                      Marshall Girtman  <a href="mailto:Marshall.girtman@specailmineservices.com">Marshall.girtman@specailmineservices.com</a></p> <p><b>Canadian Office</b>                      Tel 647-808-0965                      Fax 847-656-5094  <a href="mailto:SMSConnectors@aol.com">SMSConnectors@aol.com</a></p>

Accessories	Male	Female
Panel Mount Shells	<b>A-3242166LA</b>	<b>324094LA</b>
Protective Caps	<b>3325656-1001</b>	<b>3325656-901</b>
Pilot Short Circuiting Cap – Female Receptacle Only	<b>N/A</b>	<b>8347-301</b>

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
<b>325271</b>	2.937 – 2.625 Not Required	2.625 – 2.312 <b>324089-1</b>	2.312 – 2.000 <b>324089-2</b>	2.000 – 1.812 <b>324089-3</b>	N/A
			One (1) Supplied with Connector	One (1) Supplied with Connector	N/A

Spare Parts	Male	Female																		
Grounded Clamp Set	<b>8347-1994MF-1KV</b>	<b>8347-1994MF-1KV</b>																		
Receptable Eye Bolt	<b>8347-1997M</b>	<b>8347-1997F</b>																		
Handle Cable Inline Connector	<b>8347-1995LSS</b>																			
Handle Receptable	<b>8347-1995R</b>																			
Draw Bar Cable Inline Connector	<b>8347-1996LSS</b>																			
Draw Bar Receptable	<b>8347-1996R</b>																			
316 S.S. 45 Degree Box		<b>4547S</b>																		
Premium Hardware Kit: BOM	<table border="1"> <thead> <tr> <th>Description</th> <th>Qty</th> <th>Description</th> <th>Qty</th> <th>Description</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>SS 5/8-24 x 5/8" LG</td> <td>8</td> <td>YAD1014</td> <td>2</td> <td>HC-72</td> <td>1</td> </tr> <tr> <td>¼-20 x ½" SMSM</td> <td>2</td> <td>HC-56</td> <td>2</td> <td>¼-20 x 3/8"</td> <td>2</td> </tr> </tbody> </table>		Description	Qty	Description	Qty	Description	Qty	SS 5/8-24 x 5/8" LG	8	YAD1014	2	HC-72	1	¼-20 x ½" SMSM	2	HC-56	2	¼-20 x 3/8"	2
Description	Qty	Description	Qty	Description	Qty															
SS 5/8-24 x 5/8" LG	8	YAD1014	2	HC-72	1															
¼-20 x ½" SMSM	2	HC-56	2	¼-20 x 3/8"	2															
	<b>KIT-47</b>																			

Ratings	Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
	<b>4/0</b>	<b>325</b>	<b>1000</b>	<b>4X</b>

**Wiring Diagram**



(SMS Rated to 1000V)