

8332 UNI-LOCK CONNECTOR

8332-XXXX- XXX



600V/225A

CONDUCTORS:
(2) POWER
(1) GROUND
(1/2) PILOTS



1. Configuration	2. Color	
1-1P = Male Cable Attachable Single Pilot 1 = Male Cable Attachable Dual Pilot 5-1P = Female Panel Mount Single Pilot – Insert Only 5 = Female Panel Mount Dual Pilot – Insert Only 7-1P = Male Panel Mount Single Pilot – Insert Only 7 = Male Panel Mount Dual Pilot – Insert Only 8-1P = Female Cable Attachable Single Pilot 8 = Female Cable Attachable Dual Pilot 13-1P = Female Panel Mount Single Pilot 13 = Female Panel Mount Dual Pilot 16-1P = Male Panel Mount Single Pilot 16 = Male Panel Mount Dual Pilot G = Grounded	BLK = Standard Black RED = Red WHT = White ORG = Orange BLU = Blue GRN = Green YEL = Yellow	<p><u>Corporate Office</u> 11782 Country Club Road West Frankfort, Illinois 62896 Tel 618-932-2151 Fax 618-937-2715</p> <p><u>US Sales</u> Heath Dotson Heath.dotson@specialmineservices.com</p> <p><u>International Sales</u> Marshall Girtman Marshall.girtman@specailmineservices.com</p> <p><u>Canadian Office</u> Tel 647-808-0965 Fax 847-656-5094 SMSConnectors@aol.com</p>

Accessories	Male	Female
Panel Mount Shells	A-324119	324093
Protective Caps	3325656-6	3325656-5
Pilot Short Circuiting Cap – Female Receptacle Only	N/A	8332-9

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325286	2.000 – 1.812	1.812 – 1.625	1.625 – 1.437	1.437 – 1.250	1.250 – 1.062
	Not Required	324044-1	324044-2	324044-3	324044-4

One (1) Supplied with Connector

Ratings			
Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
2/0	225	600	4X

Wiring Diagram

