

8336 UNI-LOCK CONNECTOR

8336-XXXX- XXX

600V/75A



CONDUCTORS:
(3) POWER
(1) GROUND
(0) PILOTS



1. Configuration	2. Color	
1 = Female Panel Mount – Insert Only 2 = Female Cable Attachable 3 = Male Cable Attachable 4 = Male Panel Mount – Insert Only 8 = Female Panel Mount 13 = Male Panel Mount G = Grounded	BLK = Standard Black RED = Red WHT = White ORG = Orange BLU = Blue GRN = Green YEL = Yellow	<p><u>Corporate Office</u> 11782 Country Club Road West Frankfort, Illinois 62896 Tel 618-932-2151 Fax 618-937-2715</p> <p><u>US Sales</u> Heath Dotson Heath.dotson@specialmineservices.com</p> <p><u>International Sales</u> Marshall Girtman Marshall.girtman@specailmineservices.com</p> <p><u>Canadian Office</u> Tel 647-808-0965 Fax 847-656-5094 SMSConnectors@aol.com</p>

Accessories	Male	Female
Panel Mount Shells	A-324289	324088
Protective Caps	3325656-2	3325656-1

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325298	1.500 – 1.250 Not Required	1.250 – 1.000 313305-1	1.000 – 0.750 313305-2	0.750 – 0.562 313305-3	N/A

One (1) Supplied with Connector

Ratings			
Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
8	75	600	4X

Wiring Diagram

