

8338 UNI-LOCK CONNECTOR

8338-XXXX- XXX

600V/160A



CONDUCTORS:
(3) POWER
(1) GROUND
(0) PILOTS



1. Configuration	2. Color	
1 = Female Panel Mount – Insert Only 2 = Male Cable Attachable 3 = Female Cable Attachable 4 = Male Panel Mount – Insert Only 8 = Female Panel Mount 13 = Male Panel Mount G = Grounded	BLK = Standard Black RED = Red WHT = White ORG = Orange BLU = Blue GRN = Green YEL = Yellow	<p><u>Corporate Office</u> 11782 Country Club Road West Frankfort, Illinois 62896 Tel 618-932-2151 Fax 618-937-2715</p> <p><u>US Sales</u> Heath Dotson Heath.dotson@specialmineservices.com</p> <p><u>International Sales</u> Marshall Girtman Marshall.girtman@specailmineservices.com</p> <p><u>Canadian Office</u> Tel 647-808-0965 Fax 847-656-5094 SMSConnectors@aol.com</p>

Accessories	Male	Female
Panel Mount Shells	A-324357	324063
Protective Caps	3325656-4	3325656-3
Pilot Short Circuiting Cap – Female Receptacle Only	N/A	8344-6

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325292	1.813 – 1.562 Not Required	1.562 – 1.312 313327-1	1.312 – 1.062 313327-2	1.062 – 0.812 313327-3	0.812 – 0.625 313327-4

One (1) Supplied with Connector

Ratings

Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
2	160	600	4X

Wiring Diagram

