

8339 UNI-LOCK CONNECTOR

8339-XXXX- XXX



600V/225A

CONDUCTORS:
(3) POWER
(1) GROUND
(0) PILOTS



1. Configuration	2. Color	
1 = Male Cable Attachable 2 = Female Cable Attachable 3 = Female Panel Mount 5 = Female Panel Mount – Insert Only 6 = Male Panel Mount – Insert Only 13 = Male Panel Mount G = Grounded	BLK = Standard Black RED = Red WHT = White ORG = Orange BLU = Blue GRN = Green YEL = Yellow	<p><u>Corporate Office</u> 11782 Country Club Road West Frankfort, Illinois 62896 Tel 618-932-2151 Fax 618-937-2715</p> <p><u>US Sales</u> Heath Dotson Heath.dotson@specialmineservices.com</p> <p><u>International Sales</u> Marshall Girtman Marshall.girtman@specailmineservices.com</p> <p><u>Canadian Office</u> Tel 647-808-0965 Fax 847-656-5094 SMSConnectors@aol.com</p>

Accessories	Male	Female
Panel Mount Shells	A-324119	324093
Protective Caps	3325656-6	3325656-5

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325286	2.000 – 1.812 Not Required	1.812 – 1.625 324044-1	1.625 – 1.437 324044-2	1.437 – 1.250 324044-3	1.250 – 1.062 324044-4

One (1) Supplied with Connector

Ratings			
Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
2/0	225	600	4X

Wiring Diagram

