

8340 UNI-LOCK CONNECTOR

8340-XXXX- XXX



600V/325A

CONDUCTORS:

- (3) POWER**
- (1) GROUND**
- (0) PILOTS**



1. Configuration	2. Color	
2 = Male Panel Mount 3 = Male Panel Mount – Insert Only 4 = Female Cable Attachable 5 = Male Cable Attachable 6 = Female Panel Mount – Insert Only 10 = Female Panel Mount G = Grounded	BLK = Standard Black RED = Red WHT = White ORG = Orange BLU = Blue GRN = Green YEL = Yellow	<p><u>Corporate Office</u> 11782 Country Club Road West Frankfort, Illinois 62896 Tel 618-932-2151 Fax 618-937-2715</p> <p><u>US Sales</u> Heath Dotson Heath.dotson@specialmineservices.com</p> <p><u>International Sales</u> Marshall Girtman Marshall.girtman@specailmineservices.com</p> <p><u>Canadian Office</u> Tel 647-808-0965 Fax 847-656-5094 SMSConnectors@aol.com</p>

Accessories	Male	Female
Panel Mount Shells	A-324232	324059
Protective Caps	3325656-8	3325656-7

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325245	2.375 – 2.125	2.125 – 1.937	1.937 – 1.750	1.750 – 1.562	1.562 – 1.375
	Not Required	324153-1	324153-2	324153-3	324153-4

One (1) Supplied with Connector

Ratings			
Max. Cable AWG	Current (A)	Voltage (V)	Enclosure
4/0	325	600	4X

Wiring Diagram

