

8348 UNI-LOCK CONNECTOR

600V/500A

8348-XXXX- XXX



CONDUCTORS:
(3) POWER
(1) GROUND
(1/2) PILOTS



1. Configuration

- 2-1P = Female Cable Attachable Single Pilot
- 2 = Female Cable Attachable Dual Pilot
- 3-1P = Male Cable Attachable Single Pilot
- 3 = Male Cable Attachable Dual Pilot
- 4-1P = Male Panel Mount Single Pilot – Insert Only
- 4 = Male Panel Mount Dual Pilot – Insert Only
- 5-1P = Female Panel Mount Single Pilot – Insert Only
- 5 = Female Panel Mount Dual Pilot – Insert Only
- 7-1P = Female Panel Mount Single Pilot
- 7 = Female Panel Mount Dual Pilot
- 10-1P = Male Panel Mount Single Pilot
- 10 = Male Panel Mount Dual Pilot
- G = Grounded

2. Color

- BLK = Standard Black
- RED = Red
- WHT = White
- ORG = Orange
- BLU = Blue
- GRN = Green
- YEL = Yellow

Corporate Office
 11782 Country Club Road
 West Frankfort, Illinois 62896
 Tel 618-932-2151
 Fax 618-937-2715

US Sales
 Heath Dotson
Heath.dotson@specialmineservices.com

International Sales
 Marshall Girtman
Marshall.girtman@specailmineservices.com

Canadian Office
 Tel 647-808-0965
 Fax 847-656-5094
SMSConnectors@aol.com

Accessories

	Male	Female
Panel Mount Shells	324095	324065
Protective Caps	3325656-12	3325656-11
Pilot Short Circuiting Cap – Female Receptacle Only	N/A	8348-8

Select Grommet to Adapt I.D. of Sleeve (supplied on plug) to O.D. of Cable Being Used.

Sleeve No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.	O.D. Cable Range Grommet No.
325305	3.281 – 3.000 Not Required	3.000 – 2.812 324024-4	2.812 – 2.625 324024-5	2.625 – 2.531 324024-6	2.531 – 2.312 324024-2	2.312 – 2.125 324024-3

One (1) Supplied with
Connector

Spare Parts

Premium Hardware Kit: BOM	Description	Qty	Description	Qty	Description	Qty	KIT-48
	SS 7/8-12 x 1/2" LG	8	YAD1014	2	HC-56	2	
	1/4-20 x 1/2" SMSM	2	HC-44	2	1/4-20 x 3/8"	2	

Ratings

Max. Cable MCM	Current (A)	Voltage (V)	Enclosure
500	500	600	4X

Wiring Diagram

